

Mounting base housing - BC 17,8 UT HBUS BK - 2896241

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Installation component housing, length: 89.7 mm, with vents, Lower part, Cross connection: DIN rail bus connector, color: black, width: 17.8 mm, height: 49 mm, number of positions cross connector: 16



Why buy this product

- Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- ✓ Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting



Key Commercial Data

Packing unit	10 STK
GTIN	4 046356 096690
GTIN	4046356096690

Technical data

General

Housing type	Installation component housing
Housing material	Polycarbonate
Color (RAL)	black (9005)

Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)

Dimensions



Mounting base housing - BC 17,8 UT HBUS BK - 2896241

Technical data

Dι	me	ns	10	ns

Length	89.7 mm	
Constructional height	49 mm	
Width	17.8 mm	
Depth	89.7 mm	
Technical data		
Power dissipation without gap	2.95 W	
Standards and Regulations		

Environmental Product Compliance

Flammability rating according to UL 94

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

V0

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC B.01742



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com