RAFIX 22 FS⁺ - Stop pushbutton compact, active/inactive

1.30.273.312/2200



RR A

General information	
Form of lens	conical mushroom form
Color of lens	red
Form of collar	round
Color of arrow	transparent
Dimensions	
Mushroom Diameter	30 mm
Overall height	25.9 mm
Mounting depth	PCB 9.2 mm, QC 27 mm
Mounting hole	22.3 mm
Diameter of collar	29.8 mm
Mechanical design	
Mounting	ring nut
Contact function	latching
Illuminability	yes
Reset	by rotating
Torque for nut ring	1.2 Nm
Mechanical characteristics	
Robustness max.	100 N
Other specifications	
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Robustness	acc. to IEC 600 68-2-3 und 2-30
Storage temperature min.	-40 °C
Storage temperature max.	+80 °C
Operating life (operations)	50,000 cycle
B10	65,000 cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Salt spray	IEC 600 68-2-11
ROHS compliant	yes
REACH compliant	yes



Panel cut-out to IEC 60947-5-1



